

## Impact Test Balls



The Impact Test Ball is a specially machined ball to test impact resistance according to IEC, CSA and UL Standards. It is made of chrome-plated-steel for durability, and is fitted with an eyelet to facilitate testing for pendulum applications. Eyelet is threaded to the ball to allow attachment of a handle or force gauge. Weights are closely controlled. Other impact test balls are made without the eye, with a handle and/or made of rubber. See chart below. Contact us for more information.

Standard	Model Number	Description	Weight
UL1989, 1418, and other	<b>ITB2</b>	2 inch ball	535 grams
ATSM and UL	<b>ITB4</b>	4 inch ball with eyebolt	4.3 Kg
IEC60950	<b>ITB15</b>	50mm diameter ball	500 grams
IEC 60529	<b>ITB20</b>	50 mm ball with handle	NR
NSF/ANSI 51	<b>ITB38</b>	1 ½ inch ball	230 grams
IEC 600656 CL 18.2.3	<b>ITB40</b>	40 mm ball	265 grams

CL 18.2.3	<b>ITB49</b>	1.25 mm balls (batch of 25)	NR
UL	<b>ITB50</b>	½ inch ball (UL)	NR
UL 639	<b>ITB75</b>	19 mm (3/4 inch) ball with eye	28 grams
UL 1082	<b>ITB82</b>	Rubber Ball	149.7 grams
	<b>ITB100</b>	3 inch ball with eyebolt	NR
IEC60529	<b>ITB125</b>	12.5 mm ball	NR
IEC 60529	<b>ITB225</b>	12.5 mm ball with handle	NR
UL 858	<b>ITB325</b>	31/4" ball	2.3 Kg
BS 4147	<b>ITB630</b>	2 1/8 inch ball	630 grams
UL	<b>TB6</b>	6 mm ball	NR

\* NR – Weight Not Required



PO Box 964, Southampton, PA 18966

Phone: 800-862-0102, 215-357-5124

Fax: 215-364-7582

E-Mail: [info@ergonomicsusa.com](mailto:info@ergonomicsusa.com)

Website: [www.ergonomicsusa.com](http://www.ergonomicsusa.com)

© 2001- 2009 Ergonomics Inc. - all rights reserved