



Model	SP120VDC3000W	SP150VDC3000W	SP200VDC3000W	SP400VDC3000W	SP600VDC3000W	SP800VDC3000W
Input Voltage Range	190~265VAC	190~265VAC	190~265VAC	190~265VAC	190~265VAC	190~265VAC
Input Frequency Range	47~63Hz	47~63Hz	47~63Hz	47~63Hz	47~63Hz	47~63Hz
Power Factor	>0.98	>0.98	>0.98	>0.98	>0.98	>0.98
Output Power Range	0~3000W	0~3000W	0~3000W	0~3000W	0~3000W	0~3000W
Output Voltage Range	0~120V	0~150V	0~200V	0~400V	0~600V	0~800V
Output Current Range	0~40A	0~30A	0~24A	0~15A	0~10A	0~7.5A
Voltage Display resolution	1mV	1mV	1mV	1mV	1mV	1mV
Current Display Resolution	0.1mA	0.1mA	0.1mA	0.1mA	0.1mA	0.1mA
Voltage Programmable Resolution	3mV	3mV	4mV	8mV	12mV	16mV
Current Programmable Resolution	1mA	1mA	1mA	1mA	1mA	1mA
Voltage Setting Accuracy	0.1%+15mV	0.1%+15mV	0.1%+15mV	0.05%+100mV	0.1%+150mV	0.05%+200mV
Current Setting Accuracy	0.1%+30mA	0.1%+30mA	0.1%+24mA	0.1%+24mA	0.1%+15mA	0.1%+20mA
Voltage Measurement Accuracy	0.1%+15mV	0.1%+15mV	0.1%+15mV	0.05%+100mV	0.1%+150mV	0.05%+200mV
Current Measurement Accuracy	0.1%+30mA	0.1%+30mA	0.1%+24mA	0.1%+24mA	0.1%+15mA	0.1%+20mA
Voltage Ripple	80mVp-p/15mVrms	80mVp-p/15mVrms	150mVp-p/30mVrms	180mVp-p/80mVrms	350mVp-p/40mVrms	350mVp-p/40mVrms
Current Ripple	60mA(Full Range) 10mA(TYP value)	60mA(Full Range) 10mA(TYP value)	50mA(Full Range) 20mA(TYP value)	40mA(Full Range) 10mA(TYP value)	25mA(Full Range) 10mA(TYP value)	40mA(Full Range) 10mA(TYP value)
Voltage Load Regulation	15mV	15mV	15mV	30mV	30mV	40mV
Current Load Regulation	40mA	30mA	24mA	24mA	10mA	20mA
Line Voltage Regulation	0.02%+8mV	0.02%+8mV	0.02%+8mV	0.01%+20mV	0.01%+30mV	0.01%+40mV
Line Current Regulation	30mA	30mA	30mA	24mA	15mA	20mA
Voltage Temperature Coefficient	100ppm/°C					
Current Temperature Coefficient	150ppm/°C					
DVM Resolution	1mV	1mV	1mV	8mV	12mV	16mV
DVM Accuracy	0.1%+15mV	0.1%+15mV	0.1%+15mV	0.05%+100mV	0.05%+150mV	0.05%+200mV
Operating Mode	Constant voltage (CV) / Constant Current (CC)					
Remote Compensation	5V MAX					
Response (Voltage Rise)	≤20ms	≤25ms	≤30ms	≤60ms	≤60ms	≤60ms
Response (Voltage Drop)	≤350ms(No Load) ≤21ms(Full Load)	≤500ms(No Load) ≤25ms(Full Load)	≤500ms(No Load) ≤25ms(Full Load)	≤1200ms(No Load) ≤75ms(Full Load)	≤1200ms(No Load) ≤75ms(Full Load)	≤1200ms(No Load) ≤75ms(Full Load)
Load Transient Recovery Time	≤2ms	≤2.5ms	≤3ms	≤3ms	≤3ms	≤3ms
Command Respond Time	50ms	50ms	50ms	50ms	50ms	50ms
Efficiency (Full Load)	91%	92%	91%	91%	91%	91%
Communication Modes	1. RS232/RS485/USB/LAN; 2. RS232/RS485/USB/LAN/GPIB					
Protection Functions	OVP/OCP/OTP/OPP/SCP protection functions					
Net Weight	13.2kg	13.2kg	13.2kg	14.7kg	14.7kg	14.7kg
Weight of Accessories	1.0kg	1.0kg	1.0kg	1.0kg	1.0kg	1.0kg
Dimensions (W x H x D)	483.0x87.0x581.0 mm					
Operating Environment	Temperature: 0°C ~ 40°C Relative humidity 10%-90%(non-condensing)					
Cooling	Forced Cooling					
Certification	CE/UL/CSA/FCC/RoHS					

*Series/Parallel Capability: Can up to 10 units with output voltage less than 1000V

APM Technologies (Dongguan) Co., Ltd

Add: #7, Link Information Industry Park, Shuilianshan Road,
Nancheng, Dongguan, Guangdong, China

Tel: +86 769-2202 8588 Fax: +86 769-2202 6771

E-mail: mk@apmtech.cn Web: en.apmtech.cn