


BTS-5V5A Battery testing system			
Model:	BTS-5V5A	Battery testing system	SN: CT-9008-5V5A-SMBUS
Items		Values	
Input AC		220V +10% / -20%, 50Hz;	
Input power		300W	
Resolution		AD: 16bit; DA: 16bit	
Input Impedance		$\geq 1000M \Omega$ Power-on status (leakage current is 100uA when power-off)	
Voltage	Output range/channel	Charge: 0V~5V Discharge: 0V~5V	
	Minimum discharge voltage	0V	
	Accuracy	$\pm 0.02\%$ of range	
	Stability	0.005% of FS	
Current	Output range/channel	<b>Range1: 0.1 <math>\mu</math>A-150 <math>\mu</math>A; Range2: 150 <math>\mu</math>A-5mA; Range3: 5mA-150mA; Range4: 150mA-5A</b>	
	Accuracy	$\pm 0.02\%$ of FS Range1: $\pm 30nA$ ; Range2: $\pm 1 \mu A$ ; Range3: $\pm 30 \mu A$ ; Range4: $\pm 1mA$	
	Stability	$\pm 0.005\%$ of FS	
Power	Output power/channel	25W	
	Stability	$\pm 0.02\%$ of FS	
Temperature	Temperature probe	K type thermocouple	
	Measurement range	-40 ~ +110°C	
	Measurement accuracy	$\pm 1^\circ C$	
	Resolution	0.1°C	
	Date Record Frequency	1Hz	
Time	Current response time	$\leq 100 \mu S$ (10% to 90% or 90% to 10%);	
	Working step time	$\leq (365*24)h/step$ Time format-00: 00: 00.000(h, m, s, ms)	
Data Record	Data record conditions	Time $\Delta t$ : $\geq 1ms$	
		Voltage $\Delta U$ : $\geq 1mV$	
		Current $\Delta I$ : $\geq 100nA$	
Frequency	1000Hz (Continuous charge and discharge mode) / Pulse by pulse recording (GSM pulse mode);		
Charge	Charge modes	CC, CV, CCCV, CP, CR	
	Cut-off condition	Voltage, Current, $-\Delta t$ , Capacity, Energy, Power	

Discharge	Discharge modes	CC、CV、CR、CP、Pulse
	Cut-off condition	Voltage、Current、 $-\Delta t$ 、Capacity
Pulse Mode	Charge	CC Mode
	Discharge	CC Mode
	Minimum pulse width	400 $\mu$ s
	Pulse number	A single pulse step supports 16 different pulse segments
	Cut-off condition	Voltage、 $-\Delta t$
DCIR Test	Support DCIR step	
Cycles	Max cycles	65535
	Max steps	255
	Nest	4;
Protection	Safety protection and Anomaly protection	Power-off data protection User-defined protection conditions, such as upper and lower limited current/voltage, upper limited capacity, upper limited power, Current and voltage fluctuation, delay time, temperature, etc.
	Hardware protection	Anti-reverse connection protection, input overvoltage protection, output overvoltage protection, input overcurrent protection, output overcurrent protection, overheat protection, overload protection, output no-load protection;
Channel features	<p>Using energy-saving inverter technology, energy is locally transferred between channels, which is energy-saving and environmentally friendly;</p> <p>It adopts automotive-grade master control scheme, 200kHz high frequency conversion, low ripple and low noise;</p> <p>The equipment is small in size, low in energy consumption, and low in heat;</p> <p>Constant current source and constant voltage source adopt independent double closed loop structure;</p> <p>The system adopts an integrated design, and the unit tester directly connects to the test server on the Internet;</p> <p>High-speed 1000Hz sampling;</p> <p>1GB offline storage capacity per channel;</p>	
Channels control mode	Independent control	
Data acquisition method	Kelvin connection	
Noise	<80dB	
Communication with computer	TCP/IP	
Data Export	EXCEL、TXT、CSV、PDF、Plot/Graph	
Communication port	Ethernet 100M	
Number of channels per	8	
<b>Operation and storage environment requirement</b>		

Items	Values
Operation environment temperature	25°C ± 5°C (Accuracy Guaranteed) 25°C ± 20°C (extreme operating temperature);
Storage environment temperature	0°C ~ 60°C
Operation environment humidity	30% ~ 70% RH (no moisture condensation)
Storage environment humidity	30% ~ 80% RH (no moisture condensation)
<b>Clamps and dimensions</b>	
Items	Values
Clamps types	Choose according to customer needs
Unit tester size (W*D*H)	443 * 615 * 125 (mm)
Tester Picture (Pictures just for reference)	
<b>SMBUS characteristics</b>	
Items	Values
Hardware compatibility	Compatible with SMBUS, I2C communication protocol, support 400kHz high-speed mode;
Software compatibility	Compatible with the standard specification field information instructions defined by Smart Battery Data Specification Revision 1.1, users can edit the DBC by themselves to support different chip protocols;
Data reading frequency	4CH runs independently, each channel can be individually set to read different SMBUS parameter lists, and each parameter can be dynamically refreshed in real time or read at one time to reduce bus occupation; All channels can be read at full speed at the set bus rate (100kHz~400kHz) at the same time; When only a few parameters are read per channel, it can be refreshed more than 10 times per second;
Variable storage	Test users can define the variable list to be saved by themselves; The SMBUS variable storage and the main channel parameters of the equipment are recorded synchronously;